



SLY PleatJet II Plus Horizontal Cartridge Filter

Model No.	Standard Media * Area (Sq. Ft.)	Spun Bonded Media Area (Sq. Ft.)	Number of Hoppers	Cartridge Quantity	Air Usage (SCFM @ 80 PSIG) **
HCF-2-3-26	1356	672	1	6	4

**Based on 20 second off time between pulses and 100 millisecond pulse duration (Approx.)

*Standard based on Cellulose/Synthetic Media (Other available media may have less filter area)

MODEL NO. HCF-2-3-26
 VOLUME _____ CFM
 TEMPERATURE _____ °F
 DUST _____
 LOADING _____ GR/CF
 MEDIA AREA _____ SQ.FT.
 A/C RATIO _____ :1
 PROCESS _____

- NOTES:
- Inlet size based on 3000 fpm maximum velocity.
 - Standard exhaust connection either right or left of headers.
 - Magnehelic gauge w/ bracket, tubing & fittings.
 - Unless otherwise specified, timers shipped assembled & pre-wired to solenoid enclosure.
 - Drawing dimensions are subject to change without prior notice.
 - Delta P Module for on-demand cleaning
 - NOT FOR CONSTRUCTION

SLY INC.
 TECHNOLOGY FOR A CLEAN ENVIRONMENT
 8300 Dow Circle
 Strongsville, OH 44136
 1-800-334-2957
 In Ohio (440) 891-3200
 FAX: (440) 891-3210

HCF-500-2-3-26-A