



## SLY PleatJet II Plus Horizontal Cartridge Filter

Model No.	Standard Media * Area (Sq. Ft.)	Spun Bonded Media Area (Sq. Ft.)	Number of Hoppers	Cartridge Quantity	Air Usage (SCFM @ 80 PSIG) **
HCF-2-3-36	1728	894	1	6	12

\*\*Based on 20 second off time between pulses and 100 millisecond pulse duration (Approx.)

\*Standard based on Cellulose/Synthetic Media (Other available media may have less filter area)

MODEL NO. HCF-2-3-36  
 VOLUME \_\_\_\_\_ CFM  
 TEMPERATURE \_\_\_\_\_ °F  
 DUST \_\_\_\_\_  
 LOADING \_\_\_\_\_ GR/CF  
 MEDIA AREA \_\_\_\_\_ SQ.FT.  
 A/C RATIO \_\_\_\_\_ :1  
 PROCESS \_\_\_\_\_

- NOTES:
- Inlet size based on 3000 fpm maximum velocity.
  - Standard exhaust connection either right or left of headers.
  - Magnehelic gauge w/ bracket, tubing & fittings.
  - Unless otherwise specified, timers shipped assembled & pre-wired to solenoid enclosure.
  - Drawing dimensions are subject to change without prior notice.
  - Delta P Module for on-demand cleaning
  - NOT FOR CONSTRUCTION

**SLY** INC.  
 TECHNOLOGY FOR A CLEAN ENVIROMENT  
 8300 Dow Circle, Suite 600  
 Strongsville, OH 44136  
 1-800-334-2957  
 In Ohio (440) 891-3200  
 FAX: (440) 891-3210

HCF-500-2-3-36-C