



## SLY PleatJet II Plus Horizontal Cartridge Filter

Model No.	Standard Media * Area (Sq. Ft.)	Spun Bonded Media Area (Sq. Ft.)	Number of Hoppers	Cartridge Quantity	Air Usage (SCFM @ 80 PSIG) **
HCF-2-3-52	2712	1344	1	12	12

\*\*Based on 20 second off time between pulses and 100 millisecond pulse duration (Approx.)

\*Standard based on Cellulose/Synthetic Media (Other available media may have less filter area)

MODEL NO. HCF-2-3-52

VOLUME \_\_\_\_\_ CFM

TEMPERATURE \_\_\_\_\_ °F

DUST \_\_\_\_\_

LOADING \_\_\_\_\_ GR/CF

MEDIA AREA \_\_\_\_\_ SQ.FT.

A/C RATIO \_\_\_\_\_ :1

PROCESS \_\_\_\_\_

**NOTES:**

- Inlet size based on 3000 fpm maximum velocity.
- Standard exhaust connection either right or left of headers.
- Magnehelic gauge w/ bracket, tubing & fittings.
- Unless otherwise specified, timers shipped assembled & pre-wired to solenoid enclosure.
- Drawing dimensions are subject to change without prior notice.
- Delta P Module for on-demand cleaning
- NOT FOR CONSTRUCTION

**SLY** INC.

TECHNOLOGY FOR A CLEAN ENVIROMENT

8300 Dow Circle  
Strongsville, OH 44136  
1-800-334-2957  
In Ohio (440) 891-3200  
FAX: (440) 891-3210

HCF-500-2-3-52-A