



SLY PleatJet II Plus Horizontal Cartridge Filter

Model No.	Standard Media * Area (Sq. Ft.)	Spun Bonded Media Area (Sq. Ft.)	Number of Hoppers	Cartridge Quantity	Air Usage (SCFM @ 80 PSIG) **
HCF-2-4-36	2304	1192	1	8	12

**Based on 20 second off time between pulses and 100 millisecond pulse duration (Approx.)

*Standard based on Cellulose/Synthetic Media (Other available media may have less filter area)

MODEL NO. HCF-2-4-36
 VOLUME _____ CFM
 TEMPERATURE _____ °F
 DUST _____
 LOADING _____ GR/CF
 MEDIA AREA _____ SQ.FT.
 A/C RATIO _____ :1
 PROCESS _____

- NOTES:
- Inlet size based on 3000 fpm maximum velocity.
 - Standard exhaust connection either right or left of headers.
 - Magnehelic gauge w/ bracket, tubing & fittings.
 - Unless otherwise specified, timers shipped assembled & pre-wired to solenoid enclosure.
 - Drawing dimensions are subject to change without prior notice.
 - Delta P Module for on-demand cleaning
 - NOT FOR CONSTRUCTION

SLY INC.
 TECHNOLOGY FOR A CLEAN ENVIROMENT
 8300 Dow Circle, Suite 600
 Strongsville, OH 44136
 1-800-334-2957
 In Ohio (440) 891-3200
 FAX: (440) 891-3210

HCF-500-2-4-36-C