



SLY PleatJet II Plus Horizontal Cartridge Filter

Model No.	Standard Media * Area (Sq. Ft.)	Spun Bonded Media Area (Sq. Ft.)	Number of Hoppers	Cartridge Quantity	Air Usage (SCFM @ 80 PSIG) **
HCF-2-4-52	3616	1792	1	16	12

**Based on 20 second off time between pulses and 100 millisecond pulse duration (Approx.)

* Standard based on Cellulose/Synthetic Media (Other available media may have less filter area)

MODEL NO. HCF-2-4-52

VOLUME _____ CFM

TEMPERATURE _____ °F

DUST _____

LOADING _____ GR/CF

MEDIA AREA _____ SQ.FT.

A/C RATIO _____ :1

PROCESS _____

NOTES:

- Inlet size based on 3000 fpm maximum velocity.
- Standard exhaust connection either right or left of headers.
- Magnehelic gauge w/ bracket, tubing & fittings.
- Unless otherwise specified, timers shipped assembled & pre-wired to solenoid enclosure.
- Drawing dimensions are subject to change without prior notice.
- Delta P Module for on-demand cleaning
- NOT FOR CONSTRUCTION

SLY INC.

TECHNOLOGY FOR A CLEAN ENVIRONMENT

8300 Dow Circle

Strongsville, OH 44136

1-800-334-2957

In Ohio (440) 891-3200

FAX: (440) 891-3210

HCF-500-2-4-52-A