


## SLY PleatJet II Plus Horizontal Cartridge Filter

Model No.	Standard Media * (Sq. Ft.)	Spun Bonded Media Area* (Sq. Ft.)	Cartridge Quantity	Air Usage (SCFM @ 80 PSIG) **	A	B
HCF-4-3-26	2712	1344	12	4	85"	77"
HCF-6-3-26	4068	2016	18	4	125"	117"
HCF-8-3-26	5424	2688	24	4	165"	157"
HCF-10-3-26	6780	3360	30	4	205"	197"
HCF-12-3-26	8136	4032	36	4	245"	237"

How to Determine Your Model Number

HCF - 4 - 3 - 26  
Number of valves      Number of cartridges per row      Length of cartridges

\*\*Based on 20 second off time between pulses and 100 millisecond pulse duration (Approx.)  
 \*Standard based on Cellulose/Synthetic Media (Other available media may have less filter area)



MODEL NO. HCF- \_\_\_\_\_  
 VOLUME \_\_\_\_\_ CFM  
 TEMPERATURE \_\_\_\_\_ °F  
 DUST \_\_\_\_\_  
 LOADING \_\_\_\_\_ GR/CF  
 MEDIA AREA \_\_\_\_\_ SQ.FT.  
 NO. OF CARTRIDGES \_\_\_\_\_  
 A/C RATIO \_\_\_\_\_ :1  
 PROCESS \_\_\_\_\_

NOTES:  
 - Inlet size based on 3000 fpm maximum velocity.  
 - Standard exhaust connection either right or left of header.  
 - Six (6) leg support for model HCF-8-3 and all all units larger.  
 - Magnehelic gauge w/ bracket, tubing & fittings.  
 - Unless otherwise specified, timers shipped assembled & pre-wired to solenoid enclosure.  
 - Drawing dimensions are subject to change without prior notice.  
 - Delta P Module for on-demand cleaning  
 - NOT FOR CONSTRUCTION

**SLY** INC.  
 TECHNOLOGY FOR A CLEAN ENVIROMENT

8300 Dow Circle  
 Strongsville, OH 44136  
 1-800-334-2957  
 In Ohio (440) 891-3200  
 FAX: (440) 891-3210

HCF-500-3-26-A